



Driveway Water Drainage System

List of Tools Needed, Shopping List, and Installation Instructions

 Low Capacity

 20-22 Hours
Total Man Hours

 \$375- \$450
Material Costs

 12 Tools Needed

Tools Needed

- | | | | | |
|--|---|--|---|---|
| 
Concrete Saw | 
Saw | 
Level | 
Measuring Tape | 
Pick |
| 
PVC Glue | 
Shovel | 
Plastic or Tarp | 
Trenching Machine
Optional | 
Clear Waterproof
Silicone |
| 
Concrete | | | | |

Shopping List

Quantity needed of each part will vary based on several factors specific to your project including system length, rainfall intensity, and number of problem areas. Pipe and fittings are offered in two sizes: 3" and 4". Size availability will vary based on region and store. Ensure that component sizes are consistent throughout your drainage system.

Spee-D Channel End Cap

NDS Part Number	Description	Purchase Online
321 or 421	3" or 4" Pop-up Emitter with Elbow	Buy online
400	4" Spee-D Channel Drain	Buy online
241	2" Spee-D Channel grate	Buy online
247	Spee-D Channel End Cap	Buy online
248	Spee-D Channel Coupler	Buy online
234	Spee-D Channel Bottom Outlet	Buy online
3P02 or 4P02	3" or 4" Sewer and Drain Elbow	Buy online
Generic	3" or 4" Drain Pipe	
Generic	1/2" Rebar	

Installation Instructions

Note Before You Dig

Prior to installation, have your local utility companies locate and mark the location of existing utilities. Lay out your drainage system and mark the location of trenches and individual parts to be installed with marking paint before digging. Carefully remove grass or plants that are located where the trench will be dug so they can be replanted after installation. Trenches should be dug such that they slope a minimum of 1% away from your house. Place all excavated dirt on a tarp so that it can be used later to backfill.

To speed up installation, a trenching machine can be used to dig all trenches, especially in areas with particularly hard soil. NDS drainage products have been designed to be installed in any soil type. Due to the variety of pipe types and sizes, double check that all pipe connection points are the correct size. Please follow all installation directions included with the individual parts of your drainage system. To create watertight connections between products, apply a bead of waterproof silicone to both parts and connect.

This system requires that the elevation of the Pop-Up Emitter be lower than the elevation of the area drain or the system will not drain

Step 1: Lay out system, dig trenches and holes

Dig trench for drain pipe, 3" Pro Series Channel Drain, and Flo-Well. Dry fit (no glue) the entire drainage system from

DOWNSPOUT RUNOFF: BEST SOLUTION - STEP 1



LAY OUT SYSTEM, DIG TRENCHES AND HOLES

the 3" Pro Series Channel Drain to the pop-up emitter. The Flo-Well should be installed at least 10' away from any existing structure. Measure and cut all pipe to necessary lengths. After completing each step, glue parts together.

TIP: If installing the drain in an existing concrete area, a wet concrete saw will be required to cut the concrete prior installation.

Step 2: Install Spee-D Channel Drain

WATER ON PATIO / POOL DECK: BEST SOLUTION - STEP 2



INSTALL SPEE-D CHANNEL DRAIN

A minimum of 4-inches of concrete should surround the channel where vehicular traffic will pass over the channel. Please follow installation instructions included with the channel when installing the channel drain. The Spee-D Channel Drain should be installed a minimum of 1/4" below the finished grade of the surrounding surface. Connect the required number of channel sections together using the Spee-D Channel Couplers. Place the grates on the channel and screw in place. Install end caps at the end of the runs as needed.

Step 3: Connect elbow to drain on channel

WATER ON PATIO / POOL DECK: BEST SOLUTION - STEP 3



CONNECT ELBOW TO DRAIN ON CHANNEL

Determine the way which the channel drain will be drained (either via an End Outlet or Bottom Drain) and connect the appropriate drain pipe. Glue and connect elbows as needed. Continue drain pipe in the direction of where the Pop-Up Emitter will be installed.

Step 4: Install Pop-Up Emitter

DOWNSPOUT RUNOFF: BEST SOLUTION - STEP 5



INSTALL POP-UP EMITTER

Connect the drain pipe exiting the Flo-Well to an elbow with a weep hole. The elbow should be installed with the weep hole on the horizontal side of the elbow. Slide the Pop-up Emitter onto the elbow. An additional length of pipe can be used between the elbow and Pop-Up Emitter to bring the Pop-up emitter to the surface. The Pop-Up Emitter fits on the "bell" or "hub" end of the pipe or a pipe coupler.

TIP: To avoid damaging your Pop-Up Emitter with your lawn mower, raise the cutting level of the blades or avoid passing the mower over the Pop-Up Emitter

Step 5: Backfill and Replant

Backfill and replace any grass or plants that were removed.

TIP: DO NOT BACKFILL WITH SOIL WITH HIGH CLAY

DOWNSPOUT RUNOFF: BEST SOLUTION - STEP 6



BACKFILL AND REPLANT

CONTENT. Water must be able to easily pass through the backfilled soil.



Have Questions?

Call 1-877-412-7467 or visit us on the web NDSPRO.com